



TUYAUX EN BÉTON VIBRÉ TME

Code	Ø int. m/m	Épaisseur m/m	Longueur ml	Poids kg	Condt.
01 101 001	100	24	1,00	20	70
01 101 002	150	25	1,00	30	59
01 101 003	200	28	1,00	42	35
01 101 004	250	32	1,00	66	24
01 101 005	300	38	1,00	80	1
01 101 006	400	46	1,00	140	1
01 101 007	500	50	1,00	190	1
01 101 008	600	63	1,00	300	1



TUYAUX À COLLET EN BÉTON VIBRÉ HAUTE PRESSION (non armés)

Code	Ø int. m/m	Épaisseur m/m	Longueur ml	Poids kg	Série
61 231 203	300	48	2,00	304	135B
61 231 104	400	52	2,00	400	90B



Tuyaux armés du Ø 300 au Ø 1 000 en 2,42 (sur commande)

BUSES À PUITS (non armées) ET COUVERCLES

Code	Ø int. m/m	Épaisseur m/m	Longueur ml	Poids kg	Série
61 241 001	Ø 800	70	1,00	425	buse pleine
61 241 002	Ø 800	70	0,50	210	buse pleine
61 241 101	Ø 800	70	1,00	425	buse perfor
61 241 102	Ø 800	70	0,50	210	buse perfor
61 241 003	Ø 1 000	70	1,00	550	buse pleine
61 241 004	Ø 1 000	70	0,50	270	buse pleine
61 241 103	Ø 1 000	70	1,00	550	buse perfor
61 241 104	Ø 1 000	70	0,50	270	buse perfor
01 241 503	Ø 800	80		122	couvercle plein
01 241 501	Ø 800	80		115	couvercle a/tamp
01 241 502	Ø 1 000	80		172	couvercle a/tamp
01 241 504	Ø 1 000	80		179	S/Tampon

